

DOT MATRIX PRINTERS
24-PIN
LQ-590II/590IIN

EPSON
EXCEED YOUR VISION

**AN EFFICIENT, RELIABLE
AND AFFORDABLE PRINTER
YOU CAN RELY ON.**



The Epson LQ-590II and LQ-590IIN are designed to offer busy offices extraordinary speed, output quality and reliability. Based on Epson's experience in delivering industry-standard solutions, these printers help you run and grow your business and stay in control of your operations. Easily manage and print seven-part forms* and reports at print speeds of up to 487 characters per seconds (cps) to deliver fast results and speedy transactions. Moreover, with a high character yield of up to 5 million characters, you can do more with less.



Print



High Speed
Printing



Cost
Effective



Power
Savings



Ethernet*



Epson genuine ribbons ensure greater yield, better quality and longer lifespan.

IT'S IN THE DETAILS.

Increased Productivity

Enjoy maximum productivity with fast print speeds of up to 487 cps (10 cpi) and 128 kb memory buffer.

Long-life Reliability

Enjoy cost savings, superior print quality and minimal downtime with a MTBF of 25,000 POH.

Absolute Convenience


Experience fuss-free printing with built-in network connectivity* via Ethernet cable.

* For continuous paper only
* LQ-590IIN only.

MODEL NUMBER		LQ-590II	LQ-590IIN
Printer Technology			
Printing Method		Impact dot matrix	
Number of Pins in Head		24 pins	
Print Direction		Bi-direction	
Control Code		ESC/P2, IBM PPDS	
Printer Speed			
Ultra Speed Draft	10 cpi	550cps	
High Speed Draft	10 / 12 cpi	487 / 584 cps	
Draft	10 / 12 cpi	366 / 439 cps	
NLQ	10 / 12 cpi	121 / 145 cps	
Print Characteristics			
Character Table		1 Italic and 12 graphical character tables: Italic table, PC437 (US, StandardEurope), PC850 (Multilingual), PC860 (Portuguese), PC861 (Icelandic), PC865 (Nordic), PC863 (Canadian-French), Abicomp, BRASCI, Roman 8, ISO Latin 1, PC858, ISO 8859-15	1 Italic and 7 graphical character tables: Italic table, PC437 (US, StandardEurope), PC850 (Multilingual), PC860 (Portuguese), PC865 (Nordic), PC863 (Canadian-French), PC858, ISO 8859-15
Bitmap Fonts Draft		10, 12, 15 cpi	
Scalable Fonts		Epson Roman / Sans Serif / Roman T / Sans Serif H: 10.5pt., 8pt - 32pt. (every 2pt.)	
Barcode Fonts		EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET	
Printable Columns			
Pitch	10cpi	80 columns	
Paper Handling			
Paper Path		Manual insertion (Front or Rear in-Top out), Push Tractor (Front or rear in, top out), Pull tractor (Front, rear or bottom in, top out)	
Paper / Media		Length	Width
Cut Sheet (Single Sheet)	Entry: Front	100 - 364 mm (3.9 - 14.3")	100 - 257 mm (3.9 - 10.1")
	Entry: Rear	100 - 364 mm (3.9 - 14.3")	100 - 257 mm (3.9 - 10.1")
Cut Sheet (Multi-part Sheet)	Entry: Front	100 - 364 mm (3.9 - 14.3")	100 - 257 mm (3.9 - 10.1")
	Copies	1 Original + 5 copies	
Continuous Paper (Single Sheet / Multi-part)	Entry: Front, Rear, Bottom	101.6 - 558.8 mm (4.0 - 22.0")	101.6 - 254 mm (4.0 - 10.0")
	Copies	Original + 6 copies	
Envelope (No.6)	Entry: Rear	92mm (3.6")	165mm (6.5")
	Entry: Rear	105mm (4.1")	241mm (9.5")
Envelope (No.10)	Entry: Bottom	101.6 - 558.8 mm (4.0 - 22.0")	101.6 - 254 mm (4.0 - 10.0")
	Entry: Front, Rear	100 - 148 mm (3.9 - 5.8")	100 - 148 mm (3.9 - 5.8")
Card	Entry: Front, Rear	100 - 148 mm (3.9 - 5.8")	100 - 148 mm (3.9 - 5.8")
	Entry: Rear	127mm (5")	216mm (8.5")
Roll Paper	Entry: Rear	127mm (5")	216mm (8.5")
	Entry: Rear	127mm (5")	216mm (8.5")
Line Spacing		4.23mm (1/6") or programmable in increments of 0.0706mm (1/360")	
Acoustic Noise		55dB	
Input Data Buffer		128KB	
Interface		USB 2.0, Bi-directional parallel (IEEE-1284 nibble mode supported)	USB 2.0, Bi-directional parallel (IEEE-1284 nibble mode supported), Serial, 100base-Tx wired LAN
Ribbon Cartridge		Fabric Ribbon Cartridge (Black)	
Standard		Approx. 5 million Characters ¹	
Ribbon Life			
Reliability		50 million lines (except print head)	
Mean Print Volume Between Failure (MVBf)		25,000 Power On Hours (POH) (25% Duty)	
Mean Time Between Failure (MTBF)		400 million strokes / wire	
Print Head Life		6 switches and 10 LEDs	
Control Panel			
Environmental Conditions (Operating)		5 - 35 °C	
Temperature ²		10 - 80% RH	
Humidity ²			
Electrical Specification		AC 220 - 240 V	
Rated Voltage		50Hz - 60Hz	
Rated Frequency		49W	
Power Consumption	Operating	0.5W	
	Sleep Mode	0.1W in power off mode	
	Power Off		
Supported Operating System		Microsoft Windows XP / Vista / 7 / 8 / 10	
Printer Driver		Epson Status Monitor 3: Microsoft Windows XP / Vista / 7 / 8 / 10	
Utility		Epson Setting Utility: Microsoft Windows XP / Vista / 7 / 8 / 10	

Dimensions & Weight

Weight: Approx. 7.2kg (15.9lbs)



What's in the box

Main Unit
CD-ROM
Set-up Manual
AC Power Cable
Ribbon Cartridge
Guide Stacker
Wing
Tractor

Options and Consumables

Single Bin Cut Sheet Feeder C12C806372
Pull Tractor Unit C12C933761
Ribbon Cartridge C13S015589
High Capacity Cut Sheet Feeder C12C806382

Legend

cpi Characters per inch
(Characters per 25.4mm)
cps Characters per second
cpl Character per line

¹ Actual print yield may vary depending on usage purpose and environment

² Without condensation

© 2019 Epson Singapore Pte Ltd. All Rights Reserved.
Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Information correct as at March 2019



winpoint.com.hk

永邦系統
WINPOINT
SYSTEMS